

C4 ✓
i) In page 3, line 6, after "form" insert -- without any protecting means, release liners or spacers between the successive layers of its identical stickers 26, as shown in Figure (2) and--

C5 ✓
j) In page 3, line 9, after "a postable sticker." insert --As shown in Figures (1) to (5-A), (5-D), (6) and (7), the postable sticker of the present invention has a perimeter 22 defined by two parallel side edges 23, a top edge 24 and a bottom edge 25. It also has a first area 8, which is located immediately adjacent to the top edge 24 of perimeter 22 and extends from one of the parallel side edges 23 to the other parallel side edge 23, and a second area 9 located immediately adjacent to said first area.--

C6 ✓
k) In page 4, line 3, after "line" insert --10, extending from one of the parallel side edges 23 to the other parallel side edge 23, for example as shown in Figure (3-A),--

C7 ✓
l) In page 5, line 20, after "coating" insert --and has a perimeter 22 which is defined by two parallel side edges 23, a top edge 24 and a bottom edge 25--

C8 ✓
m) In page 6, line 5, before "or" insert -- , as shown in Figure (2),--

C9 ✓
n) In page 6, line 8, after "coating." insert -- As shown in Figure (2), a plurality of identical stickers 26 is stacked directly upon one another, in perfect perimeter registration, without having any protecting means, release liners or spacers between the successive layers of its identical stickers.--

C10 ✓
o) In page 8, line 10, after "19." insert --As shown in Figures (6) and (6-A), weakened tear line 17 extends from the top edge 24 to the bottom edge 25 of the sticker perimeter 22. Also, as shown in same Figures, weakened tear line 19 extends from one of the parallel side edges 23 to the other parallel side edge 23 and is located in its entirety within second area 9.--

3. All of the above amendments to the specification have basis in the drawings as filed and/or in other segments in the description and do not add any new matter. ✓

4. Please amend claims as follows: